



# 1081C HIGH TACK ACRYLIC TAPE

## Extra Tacky Carton Sealing Tape Without the Premium Tape Price

For more challenging substrates such as recycled content cartons, product 1081C can provide a higher level of adhesion compared to many standard 2.0, 2.3 or even 2.4 mil tapes. Designed to perform through broad temperature ranges from hot and humid to cold and damp, providing an extra secure bond.

STA acrylic adhesive provides long-term holding power in a wider temperature range than hot melts. The Proven Performance of our packaging tape is supported through the use of 100% Dow PS Acrylic Adhesives.

Request your sample today!



800-258-8273

[www.sta-tapes.com](http://www.sta-tapes.com)

## Description

Total Thickness:	1.9 mils (nominal)
Adhesive:	100% <a href="#">Dow Acrylic PS Adhesive</a>
Color(s):	Clear

## Physical Properties

Tensile Strength (lbs/in):	22	PSTC-131*	(ASTM D3759**)
Elongation (% at break):	140	PSTC-131	(ASTM D3759)
180° Peel Adhesion (oz/in):	28	PSTC-101	(ASTM D3330***)
Resistance to UV light:		Excellent	

## Application Temperature

32° F to 140° F

## Operating Temperature

-20°F to 200°F

## Typical Applications

For sealing light to moderate weight cartons requiring a higher level of performance. Designed for challenging surfaces such as boxes made from highly recycled content, the combination of film conformability and increased adhesive coat weight results in a quick, aggressive bond.

## Other Standards and Specifications

Conforms to FDA SPECS: 21 CFR 175.105 and CFR 177.1520 (clear tape only)  
Complies with environmental considerations of ASTM D 1974-14

## Application and Operating Conditions

Under normal conditions the tape should unwind and adhere to the substrate properly, and perform as normally expected. The tape should be used within 1 year of the date of shipment.

Notes: \*Shear is the tape's ability to resist the sliding of two substrates relative to each other's planes of contact (to hold flaps down). The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of STA products are beyond STA's control. It is recommended that the prospective user determine their suitability before adapting them on a commercial scale.

\*Pressure Sensitive Tape Council

\*\*ASTM Standard D3759, "Standard Test Method for Tensile Strength and Elongation of Pressure Sensitive Tapes"

\*\*\*ASTM Standard D3330, "Standard Test Method for Peel Adhesion of Pressure Sensitive Tapes"



75 Industrial Park Drive, Rogersville, TN 37857  
Phone: (800) 258-8273/(714) 249-7888 Fax: (800) 235-8273/(714) 868-8691  
STA, LLC [www.sta-tapes.com](http://www.sta-tapes.com)